TR 137 - Technische Daten

Description

TR 137 ist der BKT Reifen, der sich ausgezeichnet für alle Erntearbeiten eignet. Er bietet auch bei hohen Lasten hervorragende Traktion auf dem Feld. Der Reifen ist in unterschiedlichen Ausführungen erhältlich: die Ausführung “aramid-belted” mit Aramidbändern bietet mehr Durchstichfestigkeit und Schutz gegen alle typischen Schäden dieser Anwendung; die “HD” Ausführung bietet erstklassige Schnitt- und Reißfestigkeit sowie ein verlängertes Reifenleben.

UM

US Standard

Construction

BIAS

Machinery

Landwirtschaft: Erntemaschine

Version	STANDARD
Type	TL
Tyre Size	24.5 - 32
LI/SS	159 A8

Dimensions US Standard

Usa code	94004324
Ply Rating	14
Section Width (inch)	24.5
Overall Diameter (inch)	71.1
Static Loaded Radius (inch)	31.8
Rolling Circumference (inch)	210.4
Rim Rec	DW 21 B
Rim Alt	DW 20 B
ECE	E4-106R-002273
TRA Code	R1

Load capacity (lbs)

mph / psi	28
25	9650

Printed on 20.04.2024 06:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..