

TR 138 - Datenblatt



Description

TR 138 wurde speziell für Teleskoplader und Schaufelbagger in der Landwirtschaft entworfen und eignet sich bestens zur Bodenbearbeitung und für Spritzanwendungen. Exzellente Traktion auf weichem Boden, gute Selbstreinigungseigenschaften und Stabilität sind die Hauptmerkmale, die TR 138 zum idealen Reifen auch bei schwierigen Bodenbedingungen machen.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Baggerlader • Teleskoplader

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
17.5L - 24	STANDARD	94061877	151 A8	12	DW 15L	DW 14L	17.7	50.8	22.7	151	TL	E11-106R-005232

Printed on 27.04.2024 10:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..