

## TR 171 - Technische Daten



### Description

TR 171 ist ein Reifen mit tiefer Lauffläche, der sich für Traktoren zur Bodenbearbeitung eignet. Dank der erstklassigen Selbstreinigungseigenschaften ist er ideal für nasse und feuchte Böden. Selbst unter härtesten Einsatzbedingungen bietet TR 171 mit seiner speziellen Gummimischung ausgezeichnete Traktion und außergewöhnliche Beständigkeit.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Traktor

Version	HD
Type	TT
Tyre Size	13.6 - 28
LI/SS	122 A8

## Dimensions US Standard

Usa code	94051755
Ply Rating	8
Section Width (inch)	13.8
Overall Diameter (inch)	52.2
Static Loaded Radius (inch)	24.2
Rolling Circumference (inch)	158
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-004111
TRA Code	R1W+

## Load capacity (lbs)

mph / psi	28
25	3300

Printed on 19.04.2024 21:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..