

TR 171 - Technische Daten



Description

TR 171 ist ein Reifen mit tiefer Lauffläche, der sich für Traktoren zur Bodenbearbeitung eignet. Dank der erstklassigen Selbstreinigungseigenschaften ist er ideal für nasse und feuchte Böden. Selbst unter härtesten Einsatzbedingungen bietet TR 171 mit seiner speziellen Gummimischung ausgezeichnete Traktion und außergewöhnliche Beständigkeit.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	9.5 - 18
LI/SS	105 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	241
Overall Diameter (mm)	900
Static Loaded Radius (mm)	423
Rolling Circumference (mm)	2790
Rim Rec	W 8
ECE	E11-106R-003552
TRA Code	R1W+

Load capacity (Kg)

km/h / bar	3.00
30	925

Printed on 19.04.2024 20:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..