TR 173 - Technische Daten

Description

TR 173 ist ein Traktorenreifen, der sich bestens für feuchte Bedingungen und Reisfelder eignet. Das spezielle Laufflächenmuster bietet erstklassige Selbstreinigungseigenschaften neben reduzierter Bodenverdichtung dank einer breiten Aufstandsfläche.

UM

International Standard

Construction

BIAS

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	8.3 - 24
LI/SS	100 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	211
Overall Diameter (mm)	995
Static Loaded Radius (mm)	467
Rolling Circumference (mm)	3009
Rim Rec	W 7
Rim Alt	W 6
ECE	E11-106R-006484
TRA Code	R1W

Load capacity (Kg)

km/h / bar	2.40
30	800

Printed on 29.04.2024 16:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..