

TR 270 - Technische Daten



Description

TR 270 ist ein Traktorreifen zur Bodenbearbeitung. Er wurde speziell für maximale Leistungen auf nassem und feuchtem Boden entworfen. Unter solchen Bedingungen muss ein Reifen mit erstklassiger Haftung und verbesserten Selbstreinigungseigenschaften aufwarten. TR 270 erfüllt diese Anforderungen perfekt.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	13.6 - 46
LI/SS	122 A8

Dimensions US Standard

Usa code	94050826
Ply Rating	6
Section Width (inch)	13.6
Overall Diameter (inch)	71
Rim Rec	W12
Rim Alt	W12A
ECE	E11-106R-004343
TRA Code	R2

Load capacity (lbs)

mph / psi	22
25	3300

Printed on 19.04.2024 16:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..