

TR 270 - Technische Daten



Description

TR 270 ist ein Traktorreifen zur Bodenbearbeitung. Er wurde speziell für maximale Leistungen auf nassem und feuchtem Boden entworfen. Unter solchen Bedingungen muss ein Reifen mit erstklassiger Haftung und verbesserten Selbstreinigungseigenschaften aufwarten. TR 270 erfüllt diese Anforderungen perfekt.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	18.4 - 30
LI/SS	145 A8

Dimensions US Standard

Usa code	94032907
Ply Rating	12
Section Width (inch)	18.3
Overall Diameter (inch)	62.2
Static Loaded Radius (inch)	28.3
Rolling Circumference (inch)	188.5
Rim Rec	DW 16 L ; DW 16 A
Rim Alt	W 15 L ; DW 15 A
ECE	E11-106R-004121
TRA Code	R2

Load capacity (lbs)

mph / psi	32
25	6400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11.05.2025 06:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..