

## TR 273 - Technische Daten



### Description

TR 273 ist ein Traktorreifen für die Bodenbearbeitung, der speziell entworfen wurde, um maximale Leistungen auf nassem und feuchtem Boden zu erbringen. Unter solchen Bedingungen muss ein Reifen mit erstklassiger Haftung und verbesserten Selbstreinigungseigenschaften aufwarten. TR 273 erfüllt diese Anforderungen perfekt.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Traktor

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 12.4 - 24 |
| LI/SS     | 117 A8    |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94054114        |
| Ply Rating                   | 8               |
| Section Width (inch)         | 12.4            |
| Overall Diameter (inch)      | 47              |
| Static Loaded Radius (inch)  | 21.7            |
| Rolling Circumference (inch) | 146.5           |
| Rim Rec                      | W 11            |
| Rim Alt                      | W 10            |
| ECE                          | E11-106R-004100 |
| TRA Code                     | R2              |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 33   |
| 25        | 2830 |

Printed on 26.04.2024 11:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..