

TR 273 - Technische Daten



Description

TR 273 ist ein Traktorreifen für die Bodenbearbeitung, der speziell entworfen wurde, um maximale Leistungen auf nassem und feuchtem Boden zu erbringen. Unter solchen Bedingungen muss ein Reifen mit erstklassiger Haftung und verbesserten Selbstreinigungseigenschaften aufwarten. TR 273 erfüllt diese Anforderungen perfekt.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	14.9 - 24
LI/SS	132 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	380
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	595
Rolling Circumference (mm)	4044
Rim Rec	W 13
Rim Alt	W 12
ECE	E11-106R-004515
TRA Code	R2

Load capacity (Kg)

km/h / bar	2.3
30	2000

Printed on 26.04.2024 11:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..