

## TR 273 - Technische Daten



### Description

TR 273 ist ein Traktorreifen für die Bodenbearbeitung, der speziell entworfen wurde, um maximale Leistungen auf nassem und feuchtem Boden zu erbringen. Unter solchen Bedingungen muss ein Reifen mit erstklassiger Haftung und verbesserten Selbstreinigungseigenschaften aufwarten. TR 273 erfüllt diese Anforderungen perfekt.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	23.1 - 34
LI/SS	150 A8

## Dimensions US Standard

Usa code	94045730
Ply Rating	10
Section Width (inch)	23.2
Overall Diameter (inch)	72.8
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	221.8
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-003623
TRA Code	R2

## Load capacity (lbs)

mph / psi	20
25	7400

Printed on 26.04.2024 11:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..