

TR 315 - Technische Daten



Description

TR 315 ist ein Reifen für Rasenflächen und Anwendungen im Gartenbau, der sich für Gemeindefahrten und die Bodenbearbeitung mit landwirtschaftlichen Geräten, Grabenfräsen und Obsterntemaschinen eignet. Der TR 315 Reifen hat eine breite Kontaktfläche, die ausgezeichnete Haftung und erstklassige Stabilität unter jeglichen Bedingungen neben hervorragenden Selbstreinigungseigenschaften sichert.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte •
Erntemaschine für Obst • Grabenfräse

Version	STANDARD
Type	TL
Tyre Size	23 X 10.50 - 12

Dimensions US Standard

Usa code	94022298
Ply Rating	4
Section Width (inch)	10
Overall Diameter (inch)	23.6
Static Loaded Radius (inch)	10.7
Rolling Circumference (inch)	72.4
Rim Rec	8½ JA
Rim Alt	7 JA
ECE	E4-106R-002179

Load capacity (lbs)

mph / psi	20
10	1320

Printed on 27.04.2024 09:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..