

TR 317 - Datenblatt



Description

TR 317 eignet sich für Gemeindearbeiten und zur Bodenbearbeitung mit landwirtschaftlichen Geräten, Grabenfräsen und Obsterntemaschinen. Der TR 317 Reifen hat eine breite Kontaktfläche, die ausgezeichnete Haftung und erstklassige Stabilität unter jeglichen Bedingungen neben hervorragenden Selbstreinigungseigenschaften sichert.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte •
Erntemaschine für Obst • Grabenfräse

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.50 - 8	HD	6	7.00 I - 55 ; I - 70 ; I - 90		215	450	198	1305	TL	
18 X 8.50 - 8	STANDARD	4	7.00 I - 55 ; I - 70 ; I - 90		215	450	198	1305	TL	E11-106R-003495

Printed on 26.04.2024 04:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..