

## TR 360 - Technische Daten



### Description

TR 360 eignet sich für landwirtschaftliche Geräte in Transportanwendungen auf und abseits der Straße sowie zum Einsatz im Gartenbau. Das besondere Laufflächendesign sowie die Struktur der Karkasse sichern einen langen Produktlebenszyklus.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Landwirtschaftliche Geräte

Version	STANDARD
Type	TL
Tyre Size	18 X 7 - 8

## Dimensions US Standard

Usa code	94013104
Ply Rating	6
Section Width (inch)	7.1
Overall Diameter (inch)	18.1
Static Loaded Radius (inch)	8
Rolling Circumference (inch)	52.5
Rim Rec	5.5
ECE	E4-106R-002184

## Load capacity (lbs)

mph / psi	46
10	990

Printed on 26.04.2024 08:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..