

TR 390 - Technische Daten



Description

TR 390 ist ein agro-industrieller Reifen, der sich für Anhänger für die Beförderung von Zuckerrohr und Walzen eignet. TR 390 zeichnet sich durch hohe Tragfähigkeit und verstärkte Beständigkeit aus. Die Ausführung „dual bead HD“ mit doppeltem Wulst/HD ist besonders für industrielle Traktoren und Transportarbeiten auf Anhängern geeignet, die Ausführung „dual bead HD special“ mit doppeltem Wulst/HD speziell ist ideal für schwere Betriebsbedingungen.

UM

US Standard

Construction

❖ BIAS

Machinery

Landwirtschaft: Anhänger
Industrie: Walze

Version	STANDARD
Type	TL
Tyre Size	23.1 - 26
LI/SS	141 A8

Dimensions US Standard

Usa code	94005161
Ply Rating	8
Section Width (inch)	23.4
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	178.9
Rim Rec	DW 20 B
ECE	E11-106R-003595
TRA Code	R3

Load capacity (lbs)

mph / psi	16
25	5680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07.12.2024 02:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..