

TR 390 - Datenblatt



Description

TR 390 ist ein agro-industrieller Reifen, der sich für Anhänger für die Beförderung von Zuckerrohr und Walzen eignet. TR 390 zeichnet sich durch hohe Tragfähigkeit und verstärkte Beständigkeit aus. Die Ausführung „dual bead HD“ mit doppeltem Wulst/HD ist besonders für industrielle Traktoren und Transportarbeiten auf Anhängern geeignet, die Ausführung „dual bead HD special“ mit doppeltem Wulst/HD speziell ist ideal für schwere Betriebsbedingungen.

UM

US Standard

Construction

❖ BIAS

Machinery

Landwirtschaft: Anhänger
Industrie: Walze

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
23.1 - 26	DUAL BEAD HD	94030675	R3	157 A8	18	DW 20 B		23.4	61.4	27.2	178.9	TL	E11-106R-004607
23.1 - 26	HD DUAL BEAD SPECIAL	94030958	R3	157 A8	18	DW 20 B		23.4	61.4	27.2	178.9	TL	E11-106R-004629
23.1 - 26	STANDARD	94005161	R3	141 A8	8	DW 20 B		23.4	61.4	27.2	178.9	TL	E11-106R-003595
23.1 - 26	STANDARD	94005185	R3	149 A8	12	DW 20 B		23.4	61.4	27.2	178.9	TL	E4-106R-002317
23.1 - 26	STANDARD	94005222	R3	155 A8	16	DW 20 B		23.4	61.4	27.2	178.9	TL	E11-106R-004606
28L - 26	DUAL BEAD	94070695	R3	157 A8	16	DW 25 B	DW 23 B	28.1	61.4	27.2	178.9	TL	E4-106R-002337
28L - 26	DUAL BEAD HD	94047048	R3	168 A8	20	DW 25 B	DW 23 B	28.1	61.4	27.2	178.9	TL	E11-106R-004609
28L - 26	STANDARD	94005239	R3	150 A8	12	DW 25 B	DW 23 B	28.1	61.4	27.2	178.9	TL	E11-106R-004608

Printed on 24.04.2024 23:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..