

TR 391 - Datenblatt



Description

TR 391 ist ein agro-industrieller Reifen, der sich für den Transport und Verdichtungsarbeiten mit Anhängern für die Beförderung von Zuckerrohr und Walzen eignet. TR 391 zeichnet sich durch hohe Tragfähigkeit und ein verlängertes Reifenleben aus.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Anhänger

Industrie: Walze

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|-----------|----------|----------|--------|----|---------|-------------------------|-----|------|-----|------|-----|------|-----------------|
| 14.9 - 24 | STANDARD | R3 | 123 A6 | 6 | DW 13 | DW 11 ; DW 13 L ; DW 12 | 405 | 1270 | 574 | 3805 | 600 | TL | |
| 14.9 - 24 | STANDARD | R3 | 128 A6 | 8 | DW 13 | DW 11 ; DW 12 ; DW 13 L | 405 | 1270 | 574 | 3805 | 600 | TL | E11-106R-003365 |

Printed on 20.04.2024 12:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..