

TR 393 (B) - Technische Daten



Description

Der TR 393 (B) wurde speziell für Sämaschinen, Streuer und Arbeitsmaschinen auf und abseits der Straße entwickelt. Das spezielle Laufflächendesign bietet beste Auftriebs- und Selbstreinigungseigenschaften sowie eine lange Nutzungsdauer. Dank seiner großen Aufstandsfläche gewährleistet der TR 393 (B) eine hervorragende Traktion und minimiert die Bodenverdichtung.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Landwirtschaftliche Geräte •
Streumaschine

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	31 X 13.50 - 15
LI/SS	124 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	350
Overall Diameter (mm)	777
Rim Rec	10 LB
ECE	E11-106R-008131
TRA Code	R3

Load capacity (Kg)

km/h / bar	5.20
50	1600

Printed on 30.04.2024 11:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..