

## TR 393 - Technische Daten



### Description

TR 393 wurde speziell für Heupressen, Streumaschinen und landwirtschaftliche Geräte auf und abseits der Straße entwickelt. Das spezielle Laufflächenmuster gewährleistet hervorragende Flotation sowie ausgezeichnete Selbstreinigungseigenschaften neben einem langen Reifenleben. Dank der breiten Aufstandsfläche bietet TR 393 erstklassige Traktion und reduziert die Bodenverdichtung auf ein Minimum.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Heupresse • Landwirtschaftliche Geräte • Streumaschine

Version	STANDARD
Type	TL
Tyre Size	21.5L - 16.1 SL
LI/SS	146 B

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	546
Overall Diameter (mm)	1154
Rim Rec	W 18 CH
Rim Alt	W 16 CH
TRA Code	I2

## Load capacity (Kg)

km/h / bar	1.90
50	3000

Printed on 06.05.2024 16:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..