

## TR 393 - Datenblatt



### Description

TR 393 wurde speziell für Heupressen, Streumaschinen und landwirtschaftliche Geräte auf und abseits der Straße entwickelt. Das spezielle Laufflächenmuster gewährleistet hervorragende Flotation sowie ausgezeichnete Selbstreinigungseigenschaften neben einem langen Reifenleben. Dank der breiten Aufstandsfläche bietet TR 393 erstklassige Traktion und reduziert die Bodenverdichtung auf ein Minimum.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Heupresse • Landwirtschaftliche Geräte • Streumaschine

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
16.5L - 16.1 SL	STANDARD	I2	128 B	6	W14C	W14CH	420	1025	461	2966	TL
21.5L - 16.1 SL	STANDARD	I2	146 B	10	W 18 CH	W 16 CH	546	1154			TL

Printed on 06.05.2024 20:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..