

TR 459 - Technische Daten



Description

TR 459 wurde speziell für Bagger- und Ladearbeiten sowie Anwendungen im Bereich Gemeindefahrten/Wartung mit Traktoren und Baggerladern entworfen. Er bietet hohe Stabilität und ist in zwei Ausführungen erhältlich. Die Ausführung "special" sichert einen verlängerten Produktlebenszyklus.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Baggerlader • Traktor
Industrie: Baggerlader

Version	INDUSTRIAL
Type	TL
Tyre Size	14.9 - 24
LI/SS	145 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	390
Overall Diameter (mm)	1244
Static Loaded Radius (mm)	562
Rolling Circumference (mm)	3657
Rim Rec	DW 13
Rim Alt	DW 12 ; DW 11 ; DW 13 L
ECE	E11-106R-005333
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.90
40	2900

Printed on 27.04.2024 11:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..