

## TR 459 - Technische Daten



### Description

TR 459 wurde speziell für Bagger- und Ladearbeiten sowie Anwendungen im Bereich Gemeindefahrten/Wartung mit Traktoren und Baggerladern entworfen. Er bietet hohe Stabilität und ist in zwei Ausführungen erhältlich. Die Ausführung "special" sichert einen verlängerten Produktlebenszyklus.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Baggerlader • Traktor  
Industrie: Baggerlader

Version	INDUSTRIAL
Type	TL
Tyre Size	18.4 - 26
LI/SS	156 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	472
Overall Diameter (mm)	1425
Static Loaded Radius (mm)	628
Rolling Circumference (mm)	4346
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E4-106R-002304
TRA Code	R4

## Load capacity (Kg)

km/h / bar	2.50
40	4000

Printed on 27.04.2024 11:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..