

TR 459 - Datenblatt



Description

TR 459 wurde speziell für Bagger- und Ladearbeiten sowie Anwendungen im Bereich Gemeindefahrten/Wartung mit Traktoren und Baggerladern entworfen. Er bietet hohe Stabilität und ist in zwei Ausführungen erhältlich. Die Ausführung "special" sichert einen verlängerten Produktlebenszyklus.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Baggerlader • Traktor
Industrie: Baggerlader

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|-------------|--------------------|----------|--------|----|---------|-------------------------|-----|------|-----|------|------|-----------------|
| 400/70 - 20 | INDUSTRIAL | R4 | 149 A8 | | 13 | 12 SDC ; 13 SDC ; 14 | 404 | 1090 | 0 | 0 | TL | E11-106R-005332 |
| 14.9 - 24 | INDUSTRIAL | R4 | 137 A8 | 8 | DW 13 | DW 12 ; DW 11 ; DW 13 L | 390 | 1244 | 562 | 3657 | TL | E11-106R-005281 |
| 14.9 - 24 | INDUSTRIAL | R4 | 145 A8 | 12 | DW 13 | DW 12 ; DW 11 ; DW 13 L | 390 | 1244 | 562 | 3657 | TL | E11-106R-005333 |
| 16.9 - 24 | INDUSTRIAL | R4 | 142 A8 | 8 | DW 15 L | DW 14 L | 450 | 1310 | 590 | 3850 | TL | E11-106R-005188 |
| 16.9 - 24 | INDUSTRIAL | R4 | 145 A8 | 10 | DW 15 L | DW 14 L | 450 | 1310 | 590 | 3850 | TL | E11-106R-005211 |
| 16.9 - 24 | INDUSTRIAL | R4 | 149 A8 | 12 | DW 15 L | DW 14 L | 450 | 1310 | 590 | 3850 | TL | E11-106R-003624 |
| 17.5L - 24 | INDUSTRIAL | R4 | 139 A8 | 8 | DW 15 L | DW 14 L | 445 | 1270 | 557 | 3825 | TL | E11-106R-005212 |
| 17.5L - 24 | INDUSTRIAL | R4 | 144 A8 | 10 | DW 15 L | DW 14 L | 445 | 1270 | 557 | 3825 | TL | E11-106R-005285 |
| 17.5L - 24 | INDUSTRIAL | R4 | 148 A8 | 12 | DW 15 L | DW 14 L | 445 | 1270 | 557 | 3825 | TL | E11-106R-004659 |
| 18.4 - 24 | INDUSTRIAL | R4 | 155 A8 | 12 | DW 16 L | DW 15 L | 472 | 1375 | 610 | 4114 | TL | E11-106R-005217 |
| 19.5L - 24 | INDUSTRIAL | R4 | 147 A8 | 10 | DW 16 L | | 490 | 1333 | 585 | 4031 | TL | E11-106R-005334 |
| 19.5L - 24 | INDUSTRIAL | R4 | 151 A8 | 12 | DW 16 L | | 490 | 1333 | 585 | 4031 | TL | E4-106R-002300 |
| 19.5L - 24 | INDUSTRIAL SPECIAL | R4 | 151 A8 | 12 | DW 16 L | | 490 | 1333 | 585 | 4031 | TL | |
| 21L - 24 | INDUSTRIAL | R4 | 155 A8 | 12 | DW 18 L | | 533 | 1378 | 605 | 3995 | TL | E11-106R-003625 |
| 21L - 24 | INDUSTRIAL | R4 | 157 A8 | 14 | DW 18 L | | 533 | 1378 | 605 | 3995 | TL | E11-106R-005366 |
| 18.4 - 26 | INDUSTRIAL | R4 | 156 A8 | 12 | DW 16 L | DW 15 L | 472 | 1425 | 628 | 4346 | TL | E4-106R-002304 |
| 18.4 - 26 | INDUSTRIAL | R4 | 159 A8 | 14 | DW 16 L | DW 15 L | 472 | 1425 | 628 | 4346 | TL | E11-106R-003396 |
| 18.4 - 26 | INDUSTRIAL | R4 | 162 A8 | 16 | DW 16 L | DW 15 L | 472 | 1425 | 628 | 4346 | TL | E11-106R-006635 |
| 16.9 - 28 | INDUSTRIAL | R4 | 145 A8 | 8 | DW 15 L | DW 14 L | 440 | 1410 | 640 | 4145 | TL | E11-106R-005287 |
| 16.9 - 28 | INDUSTRIAL | R4 | 148 A8 | 10 | DW 15 L | DW 14 L | 440 | 1410 | 640 | 4145 | TL | E11-106R-005451 |
| 16.9 - 28 | INDUSTRIAL | R4 | 152 A8 | 12 | DW 15 L | DW 14 L | 440 | 1410 | 640 | 4145 | TL | E11-106R-003626 |
| 18.4 - 28 | INDUSTRIAL | R4 | 157 A8 | 12 | DW 16 L | DW 15 L | 472 | 1475 | 664 | 4495 | TL | E4-106R-002830 |
| 21L - 28 | INDUSTRIAL | R4 | 157 A8 | 12 | DW 18 A | | 535 | 1480 | 0 | 0 | TL | E11-106R-005335 |
| 16.9 - 30 | INDUSTRIAL | R4 | 153 A8 | 12 | DW 15 L | DW 14 L | 440 | 1470 | 657 | 4484 | TL | E11-106R-005288 |

Printed on 27.04.2024 08:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part,

on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..