

TR 461 - Technische Daten



Description

TR 461 ist ein BKT Reifenmuster für Anwendungen im Bereich Gemeindearbeiten/Wartung mit Traktoren sowie für Ladearbeiten mit Teleskopladern. Der Flankenschutz bietet besondere Widerstandsfähigkeit gegenüber Schnitten und Quetschungen. So wird ein längeres Reifenleben auch auf harten Oberflächen neben ausgezeichneter Stabilität gewährleistet.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Baggerlader • Teleskoplader • Traktor

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	305
Overall Diameter (mm)	987
Static Loaded Radius (mm)	435
Rolling Circumference (mm)	2902
Rim Rec	W 9
Rim Alt	11
ECE	E11-106R-005367
TRA Code	R4

Load capacity (Kg)

	km/h / bar	3.70
	10 FR	3710
	25 FR	3155
	30 FR	2970
	40 FR	2650
	10 DW	2590
	25 DW	2200
	30 DW	2070
	40 DW	1850

Printed on 09.05.2024 03:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..