

TR 461 - Technische Daten



Description

TR 461 ist ein BKT Reifenmuster für Anwendungen im Bereich Gemeindearbeiten/Wartung mit Traktoren sowie für Ladearbeiten mit Teleskopladern. Der Flankenschutz bietet besondere Widerstandsfähigkeit gegenüber Schnitten und Quetschungen. So wird ein längeres Reifenleben auch auf harten Oberflächen neben ausgezeichneter Stabilität gewährleistet.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Baggerlader • Teleskoplader • Traktor

Version	HD
Type	TL
Tyre Size	620/60 B 34
LI/SS	175 A8

Dimensions US Standard

Usa code	94067015
Overall Width (inch)	24.2
Overall Diameter (inch)	64.1
Static Loaded Radius (inch)	29.5
Rolling Circumference (inch)	194.1
Rim Rec	DW 20 B
TRA Code	R4

Load capacity (lbs)

mph / psi	58
25	15210

Printed on 16.04.2024 00:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..