

TR 678 - Datenblatt



Description

TR 678 wurde speziell für Anwendungen in der Forstwirtschaft entwickelt. Sein robustes Stollendesign verleiht hervorragende Traktions- und Selbstreinigungseigenschaften. Die starke Struktur der Karkasse steht für hohe Tragfähigkeit, während die Stahlbänder den Reifen vor Durchstößen und Schäden schützen. TR 678 zeichnet sich durch eine schnittfeste Gummimischung der Lauffläche aus, die erstklassige Schnitt- und Durchstoßfestigkeit auch auf schwierigem Gelände unter extremen Bedingungen gewährleistet.

UM

International Standard

Construction

BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte, Anhänger
Industrie: Bagger, Anhänger

SIZE	Version	TRA Code	L/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
600/40 - 22.5	DUAL BEAD	LS2	169 A8	20	AG 20.00		615	1085	483	3264	TL	
600/40 - 22.5	DUAL BEAD HD	LS2	169 A8	20	AG 20.00		615	1085	483	3264	TL	E11-106R-004619
650/45 - 22.5	STANDARD	LS2	166 B	20	20.0		650	1150	502	3302	TL	E11-106R-004400
650/45 - 22.5	STANDARD	LS2	160 D		20.0		650	1150	502	3302	TL	E11-106R-004399
650/45 - 22.5	STEEL BELTED	LS2	166 B	20	20.0		650	1150	502	3302	TL	E11-106R-004401
600/65 - 34	STEEL BELTED	LS2	166 A2 / 162 A6	16	DW 20 B		610	1644	758	4916	TL	
600/65 - 34	STEEL BELTED	LS2	170 A2 / 166 A6	20	DW 20 B		610	1644	758	4916	TL	
600/65 - 34	STEEL BELTED	LS2	164 A2/160 A6	14	DW 20 B		610	1644	758	4916	TL	E11-106R-003648
700/55 - 34	STANDARD	LS2	173 A2/ 168 A6	20	DW 24 B		700	1640	757	4890	TL	
700/55 - 34	STEEL BELTED	LS2	168 A2/163 A6	14	DW 24 B		700	1640	757	4890	TL	E11-106R-003403

Printed on 21.10.2020 06:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..