

TR 678 - Datenblatt



Description

TR 678 wurde speziell für Anwendungen in der Forstwirtschaft entwickelt. Sein robustes Stollendesign verleiht hervorragende Traktions- und Selbstreinigungseigenschaften. Die starke Struktur der Karkasse steht für hohe Tragfähigkeit, während die Stahlbänder den Reifen vor Durchstößen und Schäden schützen. TR 678 zeichnet sich durch eine schnittfeste Gummimischung der Lauffläche aus, die erstklassige Schnitt- und Durchstoßfestigkeit auch auf schwierigem Gelände unter extremen Bedingungen gewährleistet.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Anhänger
Industrie: Bagger • Anhänger

| SIZE | Version | USACode | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---------------|--------------|----------|----------|-----------------|----|----------|---------|------|------|------|-------|------|-----------------|
| 600/55 - 26.5 | STEEL BELTED | 94074112 | LS2 | 172 A2 / 165 A8 | 20 | AG 20.00 | | 23.8 | 53.1 | 0 | 0 | TL | E11-106R-008132 |
| 780/50 - 28.5 | STEEL BELTED | 94068982 | LS2 | 190 A2/ 182 A8 | 24 | AG 26.00 | | 30.3 | 59.6 | 0 | 0 | TL | E11-106R-006975 |
| 600/65 - 34 | STEEL BELTED | 94043378 | LS2 | 166 A2 / 162 A6 | 16 | DW 20 B | | 24 | 64.7 | 29.8 | 193.5 | TL | |
| 600/65 - 34 | STEEL BELTED | 94043385 | LS2 | 170 A2 / 166 A6 | 20 | DW 20 B | | 24 | 64.7 | 29.8 | 193.5 | TL | |
| 600/65 - 34 | STEEL BELTED | 94032679 | LS2 | 164 A2/160 A6 | 14 | DW 20 B | | 24 | 64.7 | 29.8 | 193.5 | TL | E11-106R-003648 |
| 710/55 - 34 | STEEL BELTED | 94069026 | LS2 | 173 A2/ 168 A6 | 20 | DW 24 B | | 27.6 | 64.6 | 29.8 | 192.5 | TL | |
| 710/55 - 34 | STEEL BELTED | 94069002 | LS2 | 168 A2/163 A6 | 14 | DW 24 B | | 27.6 | 64.6 | 29.8 | 192.5 | TL | E11-106R-007156 |

Printed on 27.04.2024 06:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..