

## **TR 678 - Datenblatt**



*Description*

TR 678 wurde speziell für Anwendungen in der Forstwirtschaft entwickelt. Sein robustes Stollendesign verleiht hervorragende Traktions- und Selbstreinigungseigenschaften. Die starke Struktur der Karkasse steht für hohe Tragfähigkeit, während die Stahlbänder den Reifen vor Durchstößen und Schäden schützen. TR 678 zeichnet sich durch eine schnittfeste Gummimischung der Lauffläche aus, die erstklassige Schnitt- und Durchstoßfestigkeit auch auf schwierigem Gelände unter extremen Bedingungen gewährleistet.

*UM*

US Standard

*Construction*

BIAS

*Machinery*

Landwirtschaft: Landwirtschaftliche Geräte, Anhänger  
Industrie: Bagger, Anhänger

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE	
600/40 - 22.5	DUAL BEAD	94051915	LS2	169 A8	20	AG 20.00		24.2	42.7	19	128.5	TL	E11-106R-004619	
600/40 - 22.5	DUAL BEAD HD	94054152	LS2	169 A8	20	AG 20.00		24.2	42.7	19	128.5	TL		
650/45 - 22.5	STANDARD	94026517	LS2	166 B	20	20.0		25.6	45.3	19.8	130	TL		E11-106R-004400
650/45 - 22.5	STANDARD	94005420	LS2	160 D		20.0		25.6	45.3	19.8	130	TL		E11-106R-004399
650/45 - 22.5	STEEL BELTED	94030170	LS2	166 B	20	20.0		25.6	45.3	19.8	130	TL		E11-106R-004401
600/65 - 34	STEEL BELTED	94043378	LS2	166 A2 / 162 A6	16	DW 20 B		24	64.7	29.8	193.5	TL		E11-106R-003648
600/65 - 34	STEEL BELTED	94043385	LS2	170 A2 / 166 A6	20	DW 20 B		24	64.7	29.8	193.5	TL		
600/65 - 34	STEEL BELTED	94032679	LS2	164 A2/160 A6	14	DW 20 B		24	64.7	29.8	193.5	TL		
700/55 - 34	STANDARD	94043507	LS2	173 A2/ 168 A6	20	DW 24 B		27.6	64.6	29.8	192.5	TL		
700/55 - 34	STEEL BELTED	94036615	LS2	168 A2/163 A6	14	DW 24 B		27.6	64.6	29.8	192.5	TL		

Printed on 21.10.2020 06:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..