

TR 882 - Technische Daten



Description

TR 882 ist ein sehr vielseitiger Reifen, der sich für die verschiedenste Anwendungen und Fahrzeuge eignet. Er wurde zur Ausstattung landwirtschaftlicher Geräte und Mähdrescher/Heupressen und Maschinen für den Zuckerrohranbau entworfen. Neben der speziellen Gummimischung, die Schäden reduziert, bietet der Reifen ausgezeichnete Beständigkeit und Traktion in jeder Feldbedingung. TR 882 ist auch in den Ausführungen "aramid-belted", "HD" und "special" erhältlich, um den spezifischen Nutzeranforderungen gerecht zu werden.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher •
Landwirtschaftliche Geräte • Anhänger
Industrie: Anhänger

| | |
|--------------------|---------------|
| Version | ARAMID BELTED |
| Type | TL |
| Tyre Size | 400/60 - 15.5 |
| LI/SS DRIVE WHEEL | 132 A8 |
| LI/SS FREE ROLLING | 145 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94030101 |
| Ply Rating | 14 |
| Section Width (inch) | 15.7 |
| Overall Diameter (inch) | 34.4 |
| Static Loaded Radius (inch) | 14.9 |
| Rolling Circumference (inch) | 102.6 |
| Rim Rec | AG 13.00 |
| ECE | E11-106R-004331 |

Load capacity (lbs)

| mph / psi | 52 |
|-----------|------|
| 5 FR | 8950 |
| 15 FR | 7610 |
| 20 FR | 7160 |
| 25 FR | 6390 |
| 5 DW | 6170 |
| 15 DW | 5250 |
| 20 DW | 4940 |
| 25 DW | 4410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 15.01.2025 19:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..