TR 882 - Technische Daten

Description

TR 882 ist ein sehr vielseitiger Reifen, der sich für die verschiedenste Anwendungen und Fahrzeuge eignet. Er wurde zur Ausstattung landwirtschaftlicher Geräte und Mähdrescher/Heupressen und Maschinen für den Zuckerrohranbau entworfen. Neben der speziellen Gummimischung, die Schäden reduziert, bietet der Reifen ausgezeichnete Beständigkeit und Traktion in jeder Feldbedingung. TR 882 ist auch in den Ausführungen “aramid-belted”, “HD” und “special” erhältlich, um den spezifischen Nutzeranforderungen gerecht zu werden.

UM

US Standard

Construction

BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher • Landwirtschaftliche Geräte • Anhänger
Industrie: Anhänger

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	132 A8
LI/SS FREE ROLLING	145 A8

Dimensions US Standard

Usa code	94019861
Ply Rating	14
Section Width (inch)	15.7
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	102.6
Rim Rec	AG 13.00
ECE	E4-106R-001879

Load capacity (lbs)

mph / psi	52
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390
5 DW	6170
15 DW	5250
20 DW	4940
25 DW	4410

Printed on 26.04.2024 12:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..