

TR 882 - Datenblatt



Description

TR 882 ist ein sehr vielseitiger Reifen, der sich für die verschiedenste Anwendungen und Fahrzeuge eignet. Er wurde zur Ausstattung landwirtschaftlicher Geräte und Mähdrescher/Heupressen und Maschinen für den Zuckerrohranbau entworfen. Neben der speziellen Gummimischung, die Schäden reduziert, bietet der Reifen ausgezeichnete Beständigkeit und Traktion in jeder Feldbedingung. TR 882 ist auch in den Ausführungen "aramid-belted", "HD" und "special" erhältlich, um den spezifischen Nutzeranforderungen gerecht zu werden.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher •
Landwirtschaftliche Geräte • Anhänger
Industrie: Anhänger

| SIZE | Version | USACode | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---------------|------------------|----------|-------------------|--------------------|----|----------|---------|------|------|------|-------|------|-----------------|
| 400/60 - 15.5 | ARAMID BELTED | 94030101 | 132 A8 | 145 A8 | 14 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E11-106R-004331 |
| 400/60 - 15.5 | ARAMID BELTED HD | 94048304 | 137 A8 | 149 A8 | 18 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E11-106R-005354 |
| 400/60 - 15.5 | HD | 94034529 | 132 A8 | 145 A8 | 14 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E4-106R-001879 |
| 400/60 - 15.5 | HD | 94030934 | 137 A8 | 149 A8 | 18 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | |
| 400/60 - 15.5 | SPECIAL | 94019915 | 132 A8 | 145 A8 | 14 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E11-106R-004332 |
| 400/60 - 15.5 | SPECIAL | 94029006 | 137 A8 | 149 A8 | 18 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E11-106R-004334 |
| 400/60 - 15.5 | STANDARD | 94019830 | 122 A8 | 134 A8 | 8 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E11-106R-004330 |
| 400/60 - 15.5 | STANDARD | 94019861 | 132 A8 | 145 A8 | 14 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E4-106R-001879 |
| 400/60 - 15.5 | STANDARD | 94019908 | 137 A8 | 149 A8 | 18 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E4-106R-001878 |

Printed on 23.04.2024 12:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..