TRAC FARM PLUS - Technische Daten

Description

TRAC FARM PLUS ist ein Traktorenreifen für die Hinterachse, der speziell für die Bodenbearbeitung und Transportanwendungen entwickelt wurde. Der Reifen weist eine tiefe Lauffläche mit doppelwinkligen Stollen auf, um mit ausgezeichneter Traktion und bestem Fahrkomfort auf der Straße aufzuwarten. Das spezielle Laufflächenmuster bietet mehr Kontakt und somit bessere Stabilität neben ausgezeichneten Selbstreinigungseigenschaften. TRAC FARM PLUS gewährleistet einen längeren Produktlebenszyklus des Reifens.

UM

US Standard

Construction

BIAS

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	14.9 - 28
LI/SS	130 A8

Dimensions US Standard

Usa code	94057436
Ply Rating	12
Section Width (inch)	15.4
Overall Diameter (inch)	54.3
Static Loaded Radius (inch)	25.3
Rolling Circumference (inch)	164.5
Rim Rec	W 13
Rim Alt	W 12 ; W 11
ECE	E11-106R-006811
TRA Code	R1

Load capacity (lbs)

mph / psi	34
25	4680

Printed on 19.04.2024 02:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..