TRAC FARM - Technische Daten

Description

TRAC FARM ist ein Reifen für schwere Betriebsbedingungen, der speziell für Traktoren zur Bodenbearbeitung und Transportanwendungen entworfen wurde. Dank der tiefen Lauffläche und der speziellen schnitt- und stichfesten Gummimischung ist der Reifen vortrefflich für schwierigste Einsatzbedingungen geeignet, was sich in einer guten Investitionsrendite während des gesamten Produktlebenszyklus zeigt. TRAC FARM wurde mit einer größeren Stollenanzahl entwickelt und bietet hervorragende Traktion und Selbstreinigungseigenschaften.

UM

International Standard

Construction

BIAS

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	18.4 - 30
LI/SS	149 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	467
Overall Diameter (mm)	1550
Static Loaded Radius (mm)	716
Rolling Circumference (mm)	4557
SRI (mm)	725
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-003628
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.30
30	3250

Printed on 26.04.2024 19:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..