

TRAC MASTER - Technische Daten



Description

TRAC MASTER ist ein Reifen zur Bodenbearbeitung und für Anwendungen im Gartenbau, der sich für Kleintraktoren und landwirtschaftliche Geräte eignet. Das Laufflächenmuster verleiht hervorragenden Bodenschutz neben großartiger Traktion auf dem Feld und erstklassigen Selbstreinigungseigenschaften.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Kleintraktor

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 33 X 15.50 - 15 |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Ply Rating | 6 |
| Section Width (mm) | 404 |
| Overall Diameter (mm) | 865 |
| Static Loaded Radius (mm) | 378 |
| Rolling Circumference (mm) | 2526 |
| Rim Rec | 13 LB |
| ECE | E4-106R-002329 |

Load capacity (Kg)

| km/h / bar | 2.10 |
|------------|------|
| 50 | 1370 |

Printed on 27.04.2024 19:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..