

## TRAC SUPER - Technische Daten

### Description

TRAC SUPER ist der erste Radialreifen, den BKT im Segment Gemeindearbeiten einführte. Die Reifenstruktur mit Stahlgürteln bietet einen optimalen, gleichmäßigen Lauf und beste Traktion. Deswegen eignet sich sein Einsatz besonders für Anwendungen auf großen Rasen- oder Grasflächen, wie z.B. Straßenränder oder Parks.



### UM

US Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Kleintraktor

Version	STANDARD
Type	TL
Tyre Size	440/50 R 17
LI/SS	135 D

## Dimensions US Standard

Usa code	94038534
Section Width (inch)	17.4
Overall Diameter (inch)	34.3
Static Loaded Radius (inch)	15.6
Rolling Circumference (inch)	105.3
Rim Rec	14.00
Rim Alt	13.00
ECE	E4-106R-000662

## Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52
40	2110	2120	2360	2790	3170	3600	4090	4380	4810
25	2870	2880	3210	3790	4320	4910	5570	5950	6540
20	3170	3200	3560	4220	4790	5460	6180	6610	7260
5	3790	3810	4240	5030	5720	6490	7360	7880	8650

Printed on 26.04.2024 05:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..