


## TUF LUG - Technische Daten



### Description

TUF LUG eignet sich für Anhänger und Leicht-LKWs in Transportanwendungen. Dieser Reifen bietet gute Traktion neben großartiger Beständigkeit und sichert einen langen Produktlebenszyklus.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Leicht-Lkw • Anhänger  
Industrie: Leicht-Lkw • Anhänger

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 7.50 - 16 |

## Dimensions US Standard

|                         |          |
|-------------------------|----------|
| Usa code                | 94014323 |
| Ply Rating              | 16       |
| Section Width (inch)    | 8.5      |
| Overall Diameter (inch) | 32.7     |
| Rim Rec                 | 6.00 G   |
| Rim Alt                 | 5.50 F   |

## Load capacity (lbs)

| mph / psi | 110  |
|-----------|------|
| 62 LS     | 3530 |
| 62 LD     | 3085 |

Printed on 26.04.2024 07:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..