

## VIJETA - Technische Daten



### Description

VIJETA ist ein Landwirtschaftsreifen, der sich bestens für Anwendungen auf und abseits der Straße eignet. Das aus 5 Rippen bestehende Muster optimiert die Gewichtsverteilung der Lasten. Darüber hinaus gewährleisten die verschleißfeste Gummimischung und die robuste Karkasse einen langen Produktlebenszyklus.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Anhänger

Version	STANDARD
Type	TT
Tyre Size	5.00 - 19
LI/SS	94 A3

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	140
Overall Diameter (mm)	755
Rim Rec	3.00

## Load capacity (Kg)

km/h / bar	3.80
15	670

Printed on 27.04.2024 11:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..