

## XL GRIP (E3) - Technische Daten



### Description

XL GRIP (E-3) ist ein speziell für starre Muldenkipper entwickelter Diagonalreifen, der Schnitte und Durchstiche auch unter härtesten Einsatzbedingungen, die eine ausgezeichnete Traktion erfordern, auf ein Minimum reduziert. Daraus resultiert ein verlängerter Produktlebenszyklus des Reifens.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Starrer Muldenkipper

Version	STANDARD
Type	TL
Tyre Size	18.00 - 33

## Dimensions US Standard

Usa code	94015825
Ply Rating	40
Overall Width (inch)	20.1
Overall Diameter (inch)	71.7
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	212
Rim Rec	13.00/2.5
TRA Code	E3

## Load capacity (lbs)

mph / psi	105	138
30	26000	-
5	-	44100

Printed on 30.11.2023 05:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..