

XL GRIP IND3 (ECH) - Technische Daten



Description

XL GRIP (IND-3) ist ein Diagonalreifen für Leercontainerstapler bei Stapel- und Hebearbeiten. Der Reifen zeichnet sich durch eine robuste Karkasse aus, die hohe Beständigkeit sowie erstklassige Stabilität im Hebemodus zu bietet.

UM

US Standard

Construction

BIAS

Machinery

Industrie: Leercontainerstapler

| | |
|------------------|-------------------|
| <i>Version</i> | INDUSTRIAL |
| <i>Type</i> | TL |
| <i>Tyre Size</i> | 16.00-25 |

Dimensions US Standard

| | |
|-------------------------------------|------------------|
| <i>Usa code</i> | 94031894 |
| <i>Ply Rating</i> | 28 |
| <i>Overall Width (inch)</i> | 18.3 |
| <i>Overall Diameter (inch)</i> | 58.5 |
| <i>Static Loaded Radius (inch)</i> | 26.9 |
| <i>Rolling Circumference (inch)</i> | 173 |
| <i>Rim Rec</i> | 11.25/2.0 |
| <i>Rim Alt</i> | 13.00/2.0 |
| <i>TRA Code</i> | IND3 |

Load capacity (lbs)

| | |
|-----------|--------------|
| mph / psi | 131 |
| 5 | 34220 |

publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..