

XL GRIP IND3 (RTG) - Technische Daten



Description

XL GRIP (IND-3) ist ein Diagonalreifen für RTG Krane. Der Reifen weist eine robuste Karkasse auf, die aus einer speziell formulierten Gummimischung entwickelt wurde und ein verlängertes Reifenleben gewährleistet.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: RTG-Kran

Version	INDUSTRIAL
Type	TL
Tyre Size	21.00 - 35

Dimensions US Standard

Usa code	94043361
Ply Rating	40
Overall Width (inch)	22.8
Overall Diameter (inch)	79.5
Static Loaded Radius (inch)	36.5
Rolling Circumference (inch)	235.4
Rim Rec	15.00/3.0
TRA Code	IND3

Load capacity (lbs)

mph / psi	144
5	72300

Printed on 25.04.2024 18:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..