

## XL GRIP (SCRAPER) - Technische Daten



### Description

XL GRIP (SCRAPER) ist ein nicht richtungsgebundener Breitreifen, der sich speziell für Schürfzüge auf jeglichem Gelände eignet. Der Reifen zeichnet sich durch eine robuste Karkasse und eine spezielle Gummimischung aus, die hohe Schnitt- und Durchstichfestigkeit gewährleisten, sowie ausgezeichnete Beständigkeit und Traktion auch bei schwersten Einsatzbedingungen. Weitere Vorteile sind erstklassige Selbstreinigungseigenschaften neben außerordentlicher Stabilität.

### UM

US Standard

### Construction

BIAS

### Machinery

OTR: Schürfzug

Version	STANDARD
Type	TL
Tyre Size	37.25 - 35

### Dimensions US Standard

Usa code	94058556
Ply Rating	36
Overall Width (inch)	37.6
Overall Diameter (inch)	93.1
Rim Rec	31.00/4.0
Rim Alt	29.00/3.5
TRA Code	E3

### Load capacity (lbs)

mph / psi		
30	43000	-
5	-	68000

*All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*