

XL GRIP (T) - Technische Daten



Description

XL GRIP (E-3) ist bestens für Kipper zur Beförderung schwerer Lasten im Bergbau geeignet. Die Gummimischung der Lauffläche wurde speziell entworfen, um Schnitte und Durchstiche auf härtestem Gelände auf ein Minimum zu reduzieren. XL GRIP (E-3) bietet ausgezeichnete Traktion und sichert einen verlängerten Produktlebenszyklus des Reifens.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Kipper

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	297
Overall Diameter (mm)	1115
Static Loaded Radius (mm)	529
Rolling Circumference (mm)	3368
Rim Rec	8.0
Rim Alt	7.5

Load capacity (Kg)

km/h / bar	7.60
90 LS/LD	3000

Printed on 25.04.2024 20:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..