XL GRIP ULTRA - Technische Daten

Description

XL GRIP ULTRA ist ein Diagonalreifen, der sich speziell für Muldenkipper bei schweren Einsatzbedingungen wie im Bergbau, in Steinbrüchen oder auf Baustellen eignet. Das nicht richtungsgebundene Laufflächenmuster verleiht hervorragende Seitentraktion und in vordere Zugrichtung. Der Reifen zeichnet sich durch eine starke Nylonkarkasse mit optimierten Verbindungselementen sowie eine spezielle Gummimischung der Lauffläche aus, um hohe Schnitt- und Durchstoßfestigkeit sowie ausgezeichnete Beständigkeit und Verschleißfestigkeit neben optimalen Selbstreinigungseigenschaften auch auf felsigem Untergrund zu gewährleisten.

UM

International Standard

Construction

BIAS

Machinery

OTR: Kipper

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	297
Overall Diameter (mm)	1115
Static Loaded Radius (mm)	529
Rolling Circumference (mm)	3368
Rim Rec	8.0
Rim Alt	7.5

Load capacity (Kg)

km/h / bar	7.60
90 LS/LD	3000

Printed on 27.04.2024 13:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..