

AGRI TRAILER - Especificaciones técnicas



Description

AGRI TRAILER ha sido específicamente desarrollado para los remolques del tractor. Este neumático es ideal para la agricultura moderna, siendo idóneo para las aplicaciones de transporte tanto por carretera como fuera de la carretera. Su robusta construcción se traduce en una elevada capacidad de carga, mientras que la banda de rodadura extra profunda permite un mejor kilometraje y un ciclo de vida más largo.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

Dimensions US Standard

Usa code	94050352
Ply Rating	18
Section Width (inch)	11.3
Overall Diameter (inch)	42.5
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

Load capacity (lbs)

mph / psi	-	-
-	-	-
-	-	-

Printed on 23/05/2024 8:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..