

## AGRIMAX ELOS - Especificaciones técnicas



### Description

AGRIMAX ELOS ha sido proyectado para ofrecer la máxima tracción en condiciones de uso particularmente problemáticas en terrenos mojados - como por ejemplo los arrozales - y pantanosos. El dibujo de la banda de rodadura ha sido estudiado para garantizar óptimas cualidades de auto-limpieza, esenciales en los trabajos realizados en terrenos fangosos y durante los desplazamientos. Para optimizar la productividad de la empresa agrícola, en el dibujo del neumático AGRIMAX ELOS se han integrado unas protecciones en los flancos para asegurar la máxima protección ante posibles daños.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	520/85 R 42 (20.8 R 42)
LI/SS	157 A8/B

## Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	1988
Static Loaded Radius (mm)	904
Rolling Circumference (mm)	5865
SRI (mm)	925
Rim Rec	DW 16 L
Rim Alt	DD 18 L ; DW 18 L
ECE	E4-106R-000793
TRA Code	R2

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	2270	2640	3015	3385	3755	4125
40	2270	2640	3015	3385	3755	4125
30	2430	2830	3225	3625	4020	4415
10 LT	3045	3540	4040	4535	5035	5530
10 HT	2430	2830	3225	3625	4020	4415

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/10/2024 22:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..