

## AGRIMAX ELOS - Ficha técnica



### Description

AGRIMAX ELOS ha sido proyectado para ofrecer la máxima tracción en condiciones de uso particularmente problemáticas en terrenos mojados - como por ejemplo los arrozales - y pantanosos. El dibujo de la banda de rodadura ha sido estudiado para garantizar óptimas cualidades de auto-limpieza, esenciales en los trabajos realizados en terrenos fangosos y durante los desplazamientos. Para optimizar la productividad de la empresa agrícola, en el dibujo del neumático AGRIMAX ELOS se han integrado unas protecciones en los flancos para asegurar la máxima protección ante posibles daños.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>420/85 R 28 (16.9 R 28)</b>	STANDARD	94040810	R2	139 A8/B	W 15 L	W 13 ; W 14 L	17.2	57.8	26.2	171.2	TL	E4-106R-000768
<b>480/70 R 34</b>	STANDARD	94070299	R2	155 A8/155 B	W 15 L	W 16 L ; W 14 L	19.7	63.2	28.9	191.7	TL	E11-106R-007532
<b>340/85 R 38 (13.6 R 38)</b>	STANDARD	94040452	R2	133 A8/B	W 12	W 11	13.9	63.1	28.9	188	TL	E4-106R-001477
<b>380/85 R 38 (14.9 R 38)</b>	STANDARD	94036134	R2	139 A8/B	W 12	W 11 ; W 13	15	65.4	30.4	196.6	TL	E4-106R-000779
<b>420/85 R 38 (16.9 R 38)</b>	STANDARD	94034512	R2	144 A8/B	W 15 L	W 13 ; W 14 L	17.2	68.3	30.9	202.2	TL	E4-106R-000780
<b>480/80 R 38 (18.4 R 38)</b>	STANDARD	94053766	R2	149 A8/B	W 16 L	W 15 L ; DW 16 L	19.3	71	32.3	210.9	TL	E11-106R-002991
<b>710/70 R 38</b>	STANDARD	94058617	R2	178 A8/B	DW 23 B	DW 25 B	28.2	79.5	36	240.3	TL	E11-106R-004896
<b>480/80 R 42 (18.4 R 42)</b>	STANDARD	94040827	R2	151 A8/B	DW 16 L	DD 16 L ; W 16 L	19.3	74.4	33.7	221.6	TL	E4-106R-001481
<b>520/85 R 42 (20.8 R 42)</b>	STANDARD	94040834	R2	157 A8/B	DW 16 L	DD 18 L ; DW 18 L	20.3	78.3	35.6	230.9	TL	E4-106R-000793
<b>520/85 R 42 (20.8 R 42)</b>	STANDARD	94075850	R2	167A8/B	DW 16 L	DD 18 L ; DW 18 L	20.3	78.3	36.2	240	TL	E11-106R-0010146
<b>520/85 R 46</b>	STANDARD	94070503	R2	169 A8/169 B	DW 16 L	DW 15 L ; DW 18 L ; W 15 L ; W 16 L ; W18 L ; DD 16 L ; DD 18 L	20.9	81.7	37.7	247.8	TL	E11-106R-007935

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/10/2024 23:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..