

## AGRIMAX FORCE - Especificaciones técnicas



### Description

AGRIMAX FORCE, el producto de punta de BKT, es un neumático radial específicamente proyectado para aplicaciones de tratamiento del terreno, de transporte y de cosecha con tractores y cosechadoras de elevada potencia, garantizando máximas prestaciones y eficiencia. Gracias a la tecnología IF, este neumático puede transportar cargas pesadas con una presión de inflado inferior en comparación con un neumático estándar reduciendo la compactación del suelo. AGRIMAX FORCE se caracteriza por la banda de rodadura reforzada y asegura una excelente tracción, elevadas propiedades de auto-limpieza y ahorros de carburante así como una conducción confortable.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Cosechadora • Tractor de alta potencia

|           |                    |
|-----------|--------------------|
| Version   | STANDARD           |
| Type      | TL                 |
| Tyre Size | IF 900/60 R 42 CFO |
| LI/SS     | 186 D              |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94022236        |
| Section Width (inch)         | 36.1            |
| Overall Diameter (inch)      | 84.5            |
| Static Loaded Radius (inch)  | 37.4            |
| Rolling Circumference (inch) | 252.6           |
| Rim Rec                      | DW 30 B         |
| Rim Alt                      | TW 30 B         |
| ECE                          | E11-106R-006494 |
| TRA Code                     | R1W             |

## Load capacity (lbs)

| mph / psi     | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 8760  | 10100 | 11620 | 12950 | 14480 | 15820 | 17710 | 19060 |
| From 40 to 25 | 9630  | 11100 | 12780 | 14240 | 15920 | 17380 | 19480 | 20900 |
| 20            | 10010 | 11540 | 13280 | 14800 | 16540 | 18080 | 20250 | 21780 |
| 12            | 10390 | 11980 | 13790 | 15380 | 17180 | 18770 | 21030 | 22620 |
| 5             | 12220 | 14090 | 16210 | 18080 | 20200 | 22070 | 24730 | 26600 |
| Upto 20 Cyc   | 12520 | 14430 | 16600 | 18510 | 20690 | 22600 | 25320 | 27230 |
| Upto 10 Cyc   | 14920 | 17200 | 19800 | 22070 | 24670 | 26940 | 30180 | 32460 |
| 5HT           | 10010 | 11540 | 13280 | 14800 | 16540 | 18080 | 20250 | 21780 |

Printed on 04/12/2023 7:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..