

AGRIMAX FORTIS - Especificaciones técnicas



Description

AGRIMAX FORTIS es vuestro compañero más fiable para todas las operaciones de preparación y tratamiento del terreno y de transporte. Diseñado para equipar los tractores más potentes de última generación, AGRIMAX FORTIS permite transportar cargas muy elevadas con velocidades hasta 65 km/h. Asegura una tracción excelente además de una duración superior y un gran confort para una experiencia perfecta de conducción. El neumático ha sido desarrollado con una carcasa reforzada de nylon que mejora la productividad en los campos y preserva el suelo gracias a una menor compactación.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador

Version	SPECIAL
Type	TL
Tyre Size	600/70 R 30
LI/SS	158 D/161 A8

Dimensions US Standard

Usa code	94058914
Section Width (inch)	24.1
Overall Diameter (inch)	63.1
Static Loaded Radius (inch)	28.5
Rolling Circumference (inch)	189.4
Rim Rec	DW 20 B
Rim Alt	DW 18 L ; W 18 L
ECE	E4-106R-001400
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	4500	5250	5910	6560	7220	7780	8620	9370
30	4730	5520	6210	6900	7580	8180	9060	9840
25	4890	5710	6430	7140	7860	8470	9380	10200
20	5180	6040	6800	7550	8310	8950	9920	10780
5 LT	6030	7030	7910	8800	9680	10430	11550	12550
5 HT	5180	6040	6800	7550	8310	8950	9920	10780

Printed on 27/04/2024 8:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..