

## AGRIMAX FORTIS - Especificaciones técnicas



### Description

AGRIMAX FORTIS es vuestro compañero más fiable para todas las operaciones de preparación y tratamiento del terreno y de transporte. Diseñado para equipar los tractores más potentes de última generación, AGRIMAX FORTIS permite transportar cargas muy elevadas con velocidades hasta 65 km/h. Asegura una tracción excelente además de una duración superior y un gran confort para una experiencia perfecta de conducción. El neumático ha sido desarrollado con una carcasa reforzada de nylon que mejora la productividad en los campos y preserva el suelo gracias a una menor compactación.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pulverizador

Version	SPECIAL
Type	TL
Tyre Size	650/85 R 38
LI/SS	173 D/176 A8

## Dimensions International Standard

Section Width (mm)	675
Overall Diameter (mm)	2071
Static Loaded Radius (mm)	935
Rolling Circumference (mm)	6184
SRI (mm)	975
Rim Rec	DW 23 B
Rim Alt	DW 21 B ; DW 20 B
ECE	E4-106R-001426
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	3120	3640	4095	4550	5005	5395	5980	6500
50	3280	3825	4300	4780	5260	5665	6280	6825
40	3410	3980	4475	4970	5470	5895	6535	7100
30	3590	4190	4710	5235	5760	6205	6880	7475
10 LT	4185	4880	5490	6100	6710	7230	8015	8710
10 HT	3590	4190	4710	5235	5760	6205	6880	7475

Printed on 27/04/2024 12:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..