

AGRIMAX RI 818 - Especificaciones técnicas



Description

AGRIMAX RI 818 es un neumático radial proyectado para las aplicaciones de irrigación con equipo de riego a pivote. El dibujo especial de la banda de rodadura proporciona una excelente tracción en ambientes húmedos y fangosos, así como extraordinarias propiedades de autolimpieza.

UM

International Standard

Construction

RADIAL

Machinery

Agricultura: Equipo de riego a pivote

Version	STANDARD
Type	TL
Tyre Size	280/85 R 24 (11.2 R 24)
LI/SS	140

Dimensions International Standard

Section Width (mm)	287
Overall Diameter (mm)	1086
Static Loaded Radius (mm)	490
Rolling Circumference (mm)	3271
SRI (mm)	525
Rim Rec	W 10
Rim Alt	W 9

Load capacity (Kg)

km/h / bar	1.6
CREEP	2500

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN) / For CREEP loads inflation pressure to be increased by +6 psi

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..