

AGRIMAX RI 818 - Ficha técnica



Description

AGRIMAX RI 818 es un neumático radial proyectado para las aplicaciones de irrigación con equipo de riego a pivote. El dibujo especial de la banda de rodadura proporciona una excelente tracción en ambientes húmedos y fangosos, así como extraordinarias propiedades de autolimpieza.

UM

US Standard

Construction

RADIAL

Machinery

Agricultura: Equipo de riego a pivote

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
280/85 R 24 (11.2 R 24)	STANDARD	94065578	140	W 10	W 9	11.3	42.8	19.3	128.8	TL
320/85 R 38 (12.4 R 38)	STANDARD	94065585	154	W 10	W 9 ; W 11	12.6	59.4	27.2	179.7	TL

Printed on 26/11/2022 9:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..